

SAFETY DATA SHEET Fuse Master Super Spray

SDS conform REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annex II - EU

SECTION 1: Identification of the substance/mixture and of the

company/undertaking	
Date issued	1.1.2017
1.1. Product identifier	
Product name	Super Spray
Chemical name	Suspended Glass Frit
Synonyms	Not Applicable
CAS no.	Not Applicable
Product Type	Liquid with powdered f

1.2. Relevant identified uses of the substance or mixture and uses advised against

frit

Use of the substance/preparation Applied and fused at 1350F / 732C to glass substrates.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Restrictions on use

Company name	Fusion Headquarters
Address	15500 NE Kincaid Rd.
Postcode	97132
City	Newberg
State	OR.
Country	USA
Tel	503-538-5281
Fax	503-538.6527
E-mail	office@fusionhewadquaers.com
Website	http://www.fusionheadquarters.com/
1.4. Emergency telephone	number
Emergency telephone	Poison Control 1-800-222-1222
Recommended use	Industrial use.

SECTION 2: Hazards identification

2.1. Classification of substance or mixture

GHS Classification	Not a hazardous substance or mixture. Non flammable.
GHS Label elements	Not a hazardous substance or mixture. Non flammable.
Inhalation	The product may contain breathable dust. Prolonged inhalation of a high concentration of dust may affect lung function. To use in complete safety, respect exposure limits.

Reserved for industrial and professional use.

2.2. Other hazards

Other hazards



SECTION 3: Composition/information on ingredients

Not known.

3.1. Substances			
Substance	Identification	Classification	Contents
Frit	(65997-18-4)	Glass frit	20-22 %
Ethyl Alcohol	(64-17-5)	F:R11	.25-02.5
Isopropyl Alcohol	(67-63-0)	F:R11	.25-02.5
Methyl Isobutyl	(108-10-1)	F:R11	Less than 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothes and rinse skin thoroughly with water.
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Particulates may cause abrasive eye injury. Take to hospital or eye specialist.
Ingestion	NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Do not induce vomiting. Rinse mouth with water. Contact physician if larger quantity has been consumed. Get medical attention if any discomfort continues.
4.2. Most important symp	toms and effects, both acute and delayed
Information for boolth noreconnol	Tract Symptometically. Do not give victim enviting to drink if he is

Information for health personnel Treat Symptomatically. Do not give victim anything to drink if he is unconscious.

4.3. Indication of any immediate medical attention and special treatment needed

Specific details on antidotes No recommendation given.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Improper extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising	g from the substance or mixture
Fire and explosion hazards	Non Flammable, combustible or explosive
Hazardous combustion products	Non Flammable.
5.3. Advice for firefighters	
Fire fighting procedures	No specific fire fighting procedure given. None required.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal protection measures Ensure adequate ventilation Follow safe handling advice and personal protective equipment recommendations.

Fuse Master Super Spray 6.2. Environmental precautions

Environmental precautionary Avoid discharge into drains, water courses or onto the ground. measures

6.3. Methods and material for containment and cleaning up

Cleaning method	Sweep up and shovel into suitable containers for disposal. Clean contaminated floor
	and objects thoroughly while observing environmental regulations.

6.4. Reference to other sections

Other instructions

Information regarding exposure / personal protection and disposal, see section 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling

Indling Do not generate dust. Do not breathe dust. Do not rely on your sight to determine

if dust is in the air. Respirable glass dust may be in the air without a visible dust cloud. Use adequate exhaust ventilation and dust collection to reducedust and respirable glass dust levels to below the permissible exposure limit ("PEL") or other applicable limit (if lower than the PEL). Maintain and test ventilation and dust collection equipment. Use all available work practices to control dust exposures, such as water sprays. Practice good housekeeping. Do not permit dust to collect on walls, floors, sills, ledges, machinery, or equipment. Keep airborne dust concentrations below permissible exposure or other applicable limits

Where necessary to reduce exposures below the PEL or other applicable limit (if lower than the PEL), wear a respirator approved for silica / glass frit containing dust when using, handling, storing or disposing of this product or bag. See Section 8, for further information on respirators. Do not alter the respirator. Do not wear a tight-fitting respirator with facial hair such as a beard or mustache that prevents a good face to face piece seal between the respirator and face. Maintain, clean, and fit test respirators in accordance with applicable standards. Wash or vacuum clothing that has become dusty.

Protective Safety Measures

Advice on general occupational Provide easy access to water supply and eye wash facilities. hygiene

7.2. Conditions for safe storage, including any incompatibilities

Storage

Keep bottle closed when not being used. Store bottle in a vertical position with the cap up.

7.3. Specific end use(s)

Specific use(s)

Not entered.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Component	OSHA PEL	ACGIH TLV	NIOSH REL
Glass Frit	<u>10 mg/m3</u> %SiO2 + 2 TWA (respirable dust) <u>30 mg/m3</u> %SiO2 + 2 TWA (total dust)	0.025 mg/m3 TWA (respirable dust)	0.05 mg/m3 TWA (respirable dust)

8.2. Exposure controls

Use adequate general or local exhaust ventilation to maintain concentrations in the workplace below the applicable exposure limits listed above.

Safety signs



Respiratory protection

Respiratory protection: If it is not possible to reduce airborne exposure levels to below the OSHA PEL or other applicable limit with ventilation, use the table below to assist you in selecting respirators that will reduce personal exposures to below the OSHA PEL. This table is part of the OSHA Respirator Standard 29CFR1910.134(d). *Assigned protection factor (APF)* means the workplace level of respiratory protection that a respirator or class of respirators is expected to provide to employees when the employer implements a continuing, effective respiratory protection program as specified by the Standard. For example, an APF of 10 means that the respirator should reduce the airborne concentration of a particulate by a factor of 10, so that if the workplace concentration of a particulate to 15 ug/m3. In additional a cartridge change-out schedule must be developed based on the concentrations in the workplace.

Type of respirator _{1, 2}	Quarter	Half	Full	Helmet/	Loose-fitting
1. Air-Purifying Respirator	5	310	50		
2. Powered Air-Purifying Respirator		50	1,000	425/1,000	25
3. Supplied-Air Respirator (SAR) or					
Type of respirator _{1, 2}	Quarter mask	Half mask	Full facepiece	Helmet/ hood	Loose-fitting facepiece
Demand mode		10	50		
 Continuous flow mode 		50	1,000	425/1,000	25
 Pressure-demand or other positive- pressure mode 		50	1,000		
4. Self-Contained Breathing					
(SCBA)					
Demand mode		10	50	50	
 Pressure-demand or other positive- 			10,000	10,000	
pressure mode (e.g., open/closed					

Hand protection

Hand protectionUse protective gloves. Chemical resistant gloves required for prolonged or
repeated contact.Eye / face protectionUse safety goggles or face shield in case of splash risk.Eye protectionUse safety goggles or face shield in case of splash risk.Skin protectionWear appropriate clothing to prevent any possibility of skin contact.Hygiene / EnvironmentalWash hands after contact.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance (physical state, color, etc.): White powder in clear liquid.

Odor: None. Boiling 212+ F Vapor Pressure (mm Hg.): 33 @20C Vapor Density (air=I): Heavier than air

Specific Gravity (H20 =1): Approximately 1.5 Percent Volatile By Volume (%): 20% Evaporation Rate (BuAc = 1): Similar to H20

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity		
Reactivity	Not reactive under normal conditions of use.	
10.2. Chemical stability		
Stability	Stable under the prescribed storage conditions.	
10.3. Possibility of hazardo	ous reactions	
Possibility of hazardous reactions	Not known.	
10.4. Conditions to avoid Conditions to avoid	Avoid generation of dust in handling and use.	
Incompatible materials		
Materials to avoid	Avoid contact with oxidising agents (e.g. nitric acid, peroxides, chromates, fluorine, chlorine trifluoride, and oxygen difluoride and hydrofluoric acid.). Strong acids.	
10.5. Hazardous decompos	sition products	
Hazardous decomposition products corrosive gas,	Silica / glass frit will dissolve in hydrofluoric acid and produce a silicon tetrafluoride.	

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Potential acute effects

Acute effects of exposure:

Inhalation: Inhalation of dust may cause respiratory tract irritation. Symptoms of exposure may include cough, sore throat, nasal congestion, sneezing, wheezing and shortness of breath.

Ingestion: Ingestion is an unlikely route of exposure. If dust is swallowed, it may irritate the mouth and throat. **Skin contact:** May dry the skin.

Eye contact: Particulates may cause abrasive injury.

Chronic effects: Prolonged inhalation of respirable crystalline silica may cause lung disease, silicosis, lung cancer and other effects as indicated below.

A. SILICOSIS

Silicosis can exist in several forms, chronic (or ordinary), accelerated, or acute:

<u>Chronic or Ordinary Silicosis</u> is the most common form of silicosis, and can occur after many years (10 to 20 or more) of prolonged repeated inhalation of relatively low levels of airborne respirable glass frit dust. It is further defined as either simple or complicated silicosis. Simple silicosis is characterized by lung lesions (shown as radiographic opacities) less than 1 centimeter in diameter, primarily in the upper lung zones. Often, simple silicosis is not associated with symptoms, detectable changes in lung function or disability. Simple silicosis may be progressive and may develop into complicated silicosis or progressive massive fibrosis (PMF). Complicated silicosis or PMF is characterized by lung lesions (shown as radiographic opacities) greater than 1 centimeter in diameter. Complicated silicosis or PMF symptoms, if present, are shortness of breath and cough. Complicated silicosis or PMF may be associated with decreased lung function and may be disabling.

Advanced complicated silicosis or PMF may lead to death. Advanced complicated silicosis or PMF can result in heart disease secondary to the lung disease (cor pumonale).

Fuse Master Super Spray

<u>Accelerated Silicosis</u> can occur with prolonged repeated inhalation of high concentrations of respirable glass frit over a relatively short period; the lung lesions can appear within five (5) years of initial exposure. Progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and progression is more rapid.

<u>Acute Silicosis</u> can occur after the repeated inhalation of very high concentrations of respirable glass frit over a short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough, weakness and weight loss. Acute silicosis is fatal.

B. CANCER

IARC - The International Agency for Research on Cancer ("IARC") concluded that "crystalline silica (glass frit) in the form of quartz or cristobalite dust is *carcinogenic to humans (Group 1)*". For further information on the

IARC evaluation, see <u>IARC Monographs on the Evaluation of Carcinogenic Risks to Humans</u>, Volume 100C,"A Review of Human Carcinogens: Arsenic, Metals, Fibres and Dusts " (2011).

NTP classifies "Silica, Crystalline (respirable size)" as Known to be a human carcinogen.

C. AUTOIMMUNE DISEASES

Several studies have reported excess cases of several autoimmune disorders -- scleroderma, systemic lupus erythematosus, rheumatoid arthritis -- among silica-exposed workers.

D. TUBERCULOSIS

Individuals with silicosis are at increased risk to develop pulmonary tuberculosis, if exposed to tuberculosis bacteria. Individuals with chronic silicosis have a three-fold higher risk of contracting tuberculosis than similar individuals without silicosis.

E. KIDNEY DISEASE

Several studies have reported excess cases of kidney diseases, including end stage renal disease, among silicaexposed workers. For additional information on the subject, the following may be consulted: "Kidney Disease and Silicosis", Nephron, Volume 85, pp. 14-19(2000).

F. NON-MALIGNANT RESPIRATORY DISEASES

The reader is referred to Section 3.5 of the NIOSH Special Hazard Review cited below for information concerning the association between exposure to crystalline silica and chronic bronchitis, emphysema and small airways disease. There are studies that disclose an association between dusts found in various mining occupations and non-malignant respiratory diseases, particularly among smokers. It is unclear whether the observed associations exist only with underlying silicosis, only among smokers, or result from exposure to mineral dusts generally (independent of the presence or absence of crystalline silica (glass frit), or the level of crystalline silica in the dust).

Sources of information:

The *NIOSH Hazard Review - Occupational Effects of Occupational Exposure to Respirable Crystalline Silica* (glass frit) published in April 2002 summarizes and discusses the medical and epidemiological literature on the health risks and diseases associated with occupational exposures to respirable crystalline silica. The *NIOSH Hazard Review* is available from NIOSH - Publications Dissemination, 4676 Columbia Parkway, Cincinnati, OH 45226, or through the NIOSH web site, <u>www.cdc.gov/niosh/topics/silica</u>, then click on the link "NIOSH Hazard Review: Health Effects of Occupational Exposure to Respirable Crystalline Silica".

The US Occupational Safety and Health Administration (OSHA) published a summary of respirable crystalline silica health effects in connection with OSHA's Proposed Rule regarding occupational exposure to respirable crystalline silica. The summary was published in the September 12, 2013 Federal Register, which can be found at www.federalregister.gov/articles/2013/09/12/2013-20997/occupational-exposure-to-respirable-crystalline-silica.

Numerical measures of toxicity:

Crystalline Silica - glass frit (quartz): LD50 oral rat >22,500 mg/kg

Delayed effects / repeated exposure

Sensitisation	Not known.
Chronic effects	None known.
Carcinogenic, Muta	agenic or Reprotoxic
Carcinogenicity	Not known.

Carcinogenicity	NOT KHOWH.
Mutagenicity	Not known.
Teratogenic properties	Not known.
Reproductive toxicity	Not known.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Glass frit is not known to be ecotoxic.

Will not bio-accumulate.

12.2. Persistence and degradability

Persistence and degradability Glass frit is not known to be degragable.

12.3. Mobility in soil	
Mobility	Glass frit is not mobile in soil.

12.4. Results of PBT and vPvB assessment

PBT assessment results

Bioaccumulative potential

This substance is not classified as PBT or vPvB.

12.5. Other adverse effects

Other adverse effects / Remarks None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Specify the appropriate methods of disposal

Discard any product, residue, disposable container or liner in full compliance with national regulations.

SECTION 14: Transport information

14.1. UN number	none
14.2. UN proper shipping	g name
ADR	Not regulated
IMDG	Not regulated
ICAO/IATA	Not regulated
14.3. Transport hazard c	lass(es)
ADR	None
Hazard no.	None
RID	None
ADN	None
IMDG	None
ICAO/IATA	None
14.4. Packing group	
ADR	None
RID	None
IMDG	None
ICAO/IATA	None
14.5. Environmental haz	ards
Comments	Not relevant
14.6. Special precaution	s for user
EmS	None known
14.7. Transport in bulk a	ccording to Annex II of MARPOL 73/78 and the IBC Code
Ship type required	Not determined
Pollution category	Not determined

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

TSCA Status: All ingredients are listed on the EPA TSCA inventory or exempt.

Fuse Master Super Spray

<u>RCRA</u>: This product is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et seq.

<u>CERCLA</u>: This product is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR §302. <u>Emergency Planning and Community Right to Know Act (SARA Title III)</u>: This product contains the following chemicals subject to SARA 302 or SARA 313 reporting: None above the de minimus concentrations.

<u>Clean Air Act</u>: This product is not processed with or does not contain any Class I or Class II ozone depleting substances.

<u>California Proposition 65</u>: Crystalline silica / glass frit (airborne particles of respirable size) is classified as a substance known to the State of California to be a carcinogen.

<u>California Inhalation Reference Exposure Level (REL)</u>: California established a chronic non-cancer effect REL of 3 µg for silica (crystalline, respirable / glass frit). A chronic REL is an airborne level of a substance at or below which no non-cancer health effects are anticipated in individuals indefinitely exposed to the substance at that level.

<u>Massachusetts Toxic Use Reduction Act</u>: Silica, crystalline/ glass frit (respirable size, <10 microns) is "toxic" for purposes of the Massachusetts Toxic Use Reduction Act.).

<u>Pennsylvania Worker and Community Right to Know Act</u>: glass frit is a hazardous substances under the Act, but it is not a special hazardous substance or an environmental hazardous substance.

<u>Texas Commission on Environmental Quality</u>: The Texas CEQ has established chronic and acute Reference Values and short term and long term Effects Screening Levels for crystalline silica / glass frit (quartz). The information can be accessed through <u>www.tceq.texas.gov</u>.

<u>CANADA</u>

Domestic Substances List: glass frit is not a naturally occurring substance, and is not on the Canadian DSL.

WHMIS Classification: D2A, because of the crystalline silica content of the material.

OTHER NATIONAL INVENTORIES

<u>Australian Inventory of Chemical Substances (AICS):</u> All of the components of this product are listed on the AICS inventory or exempt from notification requirements.

<u>China:</u> All of the components of this product are listed on the IECSC inventory or exempt from notification requirements.

Japan Ministry of International Trade and Industry (MITI): All of the components of this product are existing chemical substances as defined in the Chemical Substance Control Law Registry Number 1-548.

Korea Existing Chemicals Inventory (KECI) (set up under the Toxic Chemical Control Law): Listed on the ECL.

<u>New Zealand:</u> All of the components of this product are listed on the HSNO inventory or exempt from notification requirements.

<u>Philippines Inventory of Chemicals and Chemical Substances (PICCS)</u>: Listed for PICCS. <u>Taiwan:</u> All of the components of this product are listed on the CSNN inventory or exempt from notification requirements.

SECTION 16: Other information

Hazard symbol



Fuse Master Super Spray

Hazardous Material Information System (HMIS): Health * Health * Flammability 0 Physical Hazard 0 Protective Equipment E * Chronic hazard: For further information on health effects, see Sections 2, 8 and 11 of this SDS.

National Fire Protection Association (NFPA): Health 0 Flammability 0 Instability 0

Fusion Headquarters Disclaimer

The information and recommendations contained herein are based upon data believed to be up to- date and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by purchase, resale, use or exposure to our material. Customers and users of this material must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391 and 98/24.